

## Rigid Sheet Fine Linings and Panelling - K13

**Product Reference: Magnetik Wall Panels** 

**Manufacturer**: Rearo Laminates

Address: 29 Loanbank Quadrant, Glasgow G51 3HZ

**T:** 0141 440 0800

E: <u>commercial@rearo.co.uk</u>

Web: www.rearocommercial.co.uk

## Panels:

Height: 3000mm.Width: 1200mm.

Core material: 12mm STD MDF.

- Face: Rearo High Pressure Magnetic Laminate.

- Compensator: Rearo Balancer High Pressure Laminate.

Thickness: 14mm.Fire Rating: Class 2Colour: White Gloss

 Edge treatment: All edges square and clean cut. Long edges Grooved 2 Long. To be fitted with 4mm MDF slip feathers (included)

- Wall Support: Panel adhesive / Button fix clips. All as per the manufacturers standard fitting instructions

## Accessories:

- Extrusions: 2400mm Long. SAA (Satin Anodised Aluminium) End Caps

Marker Pens: 4 Pack of Whiteboard Pens

Microfibre Cloths: Pack of 10Eraser: Peelable Whiteboard EraserCleaner: 200ml Spray Cleaner

- Permanent Removal: Permanent Pen Removal Spray

## INSTALLATION

- Programming: Do not install wall panels before building is weathertight, wet trades have finished their work, wall and floor finishes are complete, and the building is well dried out.
- Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.
- Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.
- Fixing: Secure components using methods and fasteners recommended by the manufacturer. Prevent pulling away, bowing or other distortions to frames, panels and doors.
- Moisture and thermal movement: Make adequate allowance for future movement.